



# Australia's largest range of BAL40 bushfire rated windows and doors.

AWS has developed and tested an extensive range of Vantage, Elevate™ and ThermalHEART™ aluminium windows and doors to meet and exceed NCC requirements for compliance under Australian Standard AS3959-2018 for windows and doors in a BAL40 bushfire zone.

These products are engineered, tested and certified to withstand the conditions likely to occur in a BAL40 zone and are designed to help you protect your home whilst still delivering unprecedented style, efficiency and functionality for your lifestyle.



## Australia's largest range of BAL40 bushfire rated windows and doors.

Many Australian homes are located in areas prone to bushfire attack. In response, Australian Standard AS3959-2018 has increased the stringency around the selection of windows and doors along with other building materials for new build or renovation projects in bushfire prone areas. These changes are intended to reduce the risk of loss of life or damage to property in bushfire areas.

AWS has developed and tested Australia's largest range of BAL-40 Bushfire rated windows and doors, certified to withstand the conditions likely to occur in a BAL-40 zone whilst maintaining unprecedented style, efficiency and functionality for your lifestyle.

For more information about BAL-40 rated windows and doors visit our websites or speak to your local manufacturer.

[vantagewindows.com.au](http://vantagewindows.com.au)  
[elevatealuminium.com.au](http://elevatealuminium.com.au)  
[thermalheart.com.au](http://thermalheart.com.au)  
[specifyaws.com.au](http://specifyaws.com.au)



All AWS BAL40 rated windows and doors are identified with the BAL40 symbol. This symbol indicates the system has been tested or third party certified for BAL40 compliance.

## BAL40 rated systems for residential and commercial applications:

### Vantage®



#### Windows

Series 502/504/506 Residential Sliding Window  
Series 601/602 Magnum™ Sliding Window  
Series 516/517 Residential Awning Window  
Series 616/616TR Magnum™ Awning Window  
Series 514 Residential Double Hung Window  
Series 613 Magnum™ Double Hung Window  
Series 516/517 Residential Fixed Window  
Series 616 Residential Fixed Window

#### Doors

Series 548 High Performance Bifold Door  
Series 542 DStacker Sliding Door  
Series 618 Magnum™ Sliding Door  
Series 549 Hinged Entry Door  
Series 548 High Performance Door

### Elevate™



#### Windows

Series 452 Architectural Sliding Window  
Series 461 Commercial Sliding Window  
Series 456 Commercial Awning Window  
Series 466/665 Architectural Awning Window  
Series 453 Commercial Double Hung Window  
Series 463 Architectural Double Hung Window

#### Doors

Series 410/411/412 Architectural Bifold Door  
Series 442/471/642 Commercial Sliding Door  
Series 704T/704B/704R SlideMASTER™ Sliding Door  
Series 50 Commercial Door Panel (Spigoted)  
Series 51 Commercial Door Panel (Non-Spigoted)  
Series 52 Commercial Door Panel (Double Glazed, Spigoted)  
Series 650 Architectural Hinged Door

### ThermalHEART™



#### Windows

Series 726 Awning Window  
Series 726 Fixed Window

#### Doors

Series 730 Thermally Broken Bifold Door  
Series 731 Thermally Broken Sliding Door  
Series 729 Thermally Broken Hinged Door  
Series 852 Thermally Broken Door Panel

NOTE: Products may require specific glass or hardware selections to comply, your glass selection may be limited. You must specify BAL40 compliance as a requirement when placing your order. AWS BAL-40 products are suitable for use in BAL-12.5 and BAL-29.