



KEY FEATURES


- A high performance, top hung sliding door with recessed top and bottom rails and jamb stiles.
- The custom Centor E3 quad rollers are fully adjustable up and down when the door is in the frame and are capable of supporting panels up to 320kg.
- The extra strong multi hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas, refer panel strength tables.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF, XXXF, FXXX, FXXXXXXF and corner doors).
- We can fit Centor S4 roller screens behind Series 704FTH sliding doors.
- Doors fitted with custom mortice lock at meeting stiles. Lock only accessible from the inside. Alternative slimline slimline stiles with built-in finger grip inside and out. An alternative wide jamb lock stile will accept conventional mortice locks that can be accessed from inside or outside
- With the correct glass, glass size, seals and hardware, Series 704FTH can achieve BAL40 certification.




The door head is fully concealed into the building envelope to ensure clear glass sight lines right to the ceiling.



Large sliding panels are supported at the head with heavy duty rollers for smooth operation.



When recessed into the floor, clear glass sight lines can be achieved and the sill can be combined with a FlowTHRU™ drain for the ultimate flush sill transition.



The stiles and jamb are fully recessed into the building envelope to create clear sight lines around the entire door to maximise views and deliver excellent energy efficiency.

GENERAL

Max Frame Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
24mm

Frame Depth
Various

ENERGY

UW Range
2.0-3.5

SHGC Range
0.22-0.74

WEATHER

Maximum Water
300Pa

ACOUSTICS

24.38mm IGU with 6.38mm lam
Rw33 (-1;-3)

24.38mm IGU with 10.38mm lam
Rw35 (0;-2)

Based on tests carried out on the standard Series 704 door



*Dimensions subject to individual site conditions.
BAL-40 compliance may limit glass options. Maximum glass size for BAL-40 products is 5m²
elevatealuminium.com.au/704FTH