



### KEY FEATURES


- CentreGLAZE Double Glazed shopfront framing system.
- Basic 101.60 x 50mm (102 x 50) framing system with a large variety of accessories including sub-frames, COC transom, matching doors that will also accept up to 36mm double glazing and a variety of door thresholds.
- Glazing pocket designed to accept up to 44mm Insulated Glass Units (IGUs) with 12mm bite plus another 4mm to cover glass production, installation tolerances.
- Pocket reducer available for thinner IGU glazing options.
- Compatible with a large range of Elevate™ Framing systems, including sliding and bi-fold doors.
- 50mm thick door designed to accept double glazing and a wide variety of industry standard hardware options.
- Successfully tested up to 450Pa water.




Basic 102 x 50 frame will accommodate a wide range of accessories including sub frames, COC transom and matching doors and is compatible with a wide range of Elevate™ Systems.



Wide 50mm glazing pocket accommodates IGUs up to 44mm thick, ideal for applications where high performance glazing packs are used to improve energy efficiency or acoustic performance.



Pocket reducer makes it possible to reduce the glazing pocket dimension so thinner IGUs can be accommodated.



Alternative fully beaded option available on individual fixed lite windows.

#### GENERAL

**Max Panel Height**  
Various

**Max Panel Width**  
Various

**Max Glass Thickness**  
44mm

**Frame Depth**  
102mm

#### ENERGY

**UW Range**  
1.8 - 2.0

**SHGC Range**  
0.21 - 0.49

#### WEATHER

**Maximum Water**  
450Pa.

#### ACOUSTICS

This product has not been acoustics tested.