



KEY FEATURES


- This high performance awning and casement window has been designed to accept Truth™ hardware. This allows us to offer very large casements and awnings fitted with scissor type winders with jamb to stile latches that secure the sashes in the closed position.
- The extra strong sashes allow large sash windows to be fabricated for high wind load areas. Two sash designs cover awnings and casements.
- Series 668 accepts optional flyscreens.
- The Truth™ hardware can resist high negative wind loads with the use of winders and side latches.
- Hardware comes in standard E-GARD™ or for extreme locations we also offer 304 stainless steel stays, winder arms, tie rods and keepers.
- Casement sashes open to 90° and have an opening gap of approximately 80mm on the hinge side, this allows cleaning of external glass face from inside the building.
- Fixed lowlights/sidelights are designed around Series 606 single glazed and 626 double glazed FrontGLAZE™.




Accepts glass up to 24mm IGU.



Also available with 100mm frame – see Series 468.



Snap-in jamb adaptors make it possible to have SG or DG fixed highlights and/or lowlights within the same frame.



Designed to suit AWS FrontGLAZE™ framing systems.

GENERAL

NB: Maximum panel height and width of Awning sashes are interdependent.

Max Panel Height*
A/ @2400w = 800H
C/ 2100mm

Max Panel Width*
A/ @2100h = 1200w
C/ 1200mm

Max Glass Thickness
24mm

Frame Depth
150mm

ENERGY
UW Range

SHGC Range

WEATHER

Maximum Water
450Pa.

ACOUSTICS

This product has not been acoustics tested.