


KEY FEATURES


- Top hung sliding door with a bottom rail that is completely recessed into the sill.
- The custom Centor E3 quad rollers are fully adjustable up and down when doors are in the frame.
- Tested for compliance with the relevant Australian Standards.
- The extra strong multi hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas, refer panel strength tables earlier in this Section.
- There are a large variety of door combinations (XF, FX, FXXX, XXF, FXX, FXXXXF and cavity sliding doors).
- Compatible with Centor SIE screens up to 7500mm wide.
- Square clean lines with soft radius edges on internal meeting stile corners.




An ideal solution for Architecturally designed homes with living spaces which transition from internal to external



Bottom rail is recessed fully into sill to achieve a clean sight line and minimal appearance



Can be installed with a FlowTHRU™ drain for the ultimate flush threshold solution.



Doors run on heavy duty overhead rollers, delivering smooth, reliable operation

GENERAL

Max Panel Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
28mm

Frame Depth
Various

ENERGY

UW Range
3.0-6.2

SHGC Range
0.15-0.59

WEATHER

Maximum Water
300 Pa.

ACOUSTICS

6.38mm Lam
30 (0;-1)

10.38mm Lam
31 (-1;-1)

10.5mm VLam Hush™
33 (0;-2)

