


### KEY FEATURES


- This high-performance sliding door has been tested for compliance with the relevant Australian Standards.
- The extra strong multi-hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas.
- There are a large variety of door combinations possible. XF, FX, FXF, FXXF, XXF, FXX, XXXF, FXXX, FXXXXXXF and FXXXXXF. 90° corner units FX^XF and FXX^XXF are also available.
- Doors can be fitted with surface mounted deadlock, mortice lock or multi-point mortice lock.
- Doors run on heavy duty double or quad bogey wheel carriages.
- Variety of bottom rail and midrail sizes available. The tall square bottom rail is standard.
- Thresholds and snap-in flat filler ensure that the clean looks are maintained.
- Doors can be fitted with external sliding or internal Centor™ SIE retractable roller fly doors.




A unique, self-draining sub-sill is a feature of the 704.



The image above shows ICON™ recessed pull handle option used with commercial mortice lock. On heavy doors we recommend D-Pull handles.



We offer a variety of meeting stile combinations to cover most areas in Australia.



Standard tall, small, beveled and square rails are all an option. Standard tall square bottom rail illustrated above.

#### GENERAL

**Max Panel Height\***  
3300mm

**Max Panel Width\***  
2500mm

**Max Glass Thickness**  
28mm

**Frame Depth**  
Various

#### ENERGY

**UW Range**  
3.0-6.2

**SHGC Range**  
0.15-0.59

#### WEATHER

**Maximum Water**  
450 Pa.

#### ACOUSTICS

**6.38mm Lam**  
30 (0;-1)

**10.38mm Lam**  
31 (-1;-1)

**10.5mm VLam Hush™**  
33 (0;-2)

