



KEY FEATURES


- Elevate™ Double glazed FrontGLAZE™ shopfront framing system with 36mm wide glazing pocket is designed to accept up to 30mm thick Insulating Glass Units (IGUs) with the required 12mm bite.
- Frames have been tested for compliance with Australian Standard AS2047. Achieved 1200 Pa. water resistance and compliance with air-conditioning requirement.
- The 225 x 60mm framing system is designed for high wind load areas with an extra strong interlocking mullion. The product is ideal for car showrooms, foyers and mezzanine installations.
- Mullions supported with heavy duty angle brackets.
- Heavy duty transom designed to carry heavy pieces of glass.
- Glazing pocket reducers allow thinner glass (as low as 6mm thick) to be installed.
- Framing will accept pivot swing doors using 150mm wide COC closer transom.
- Double glazed awning sashes inserts available.




225mm x 60mm mullion is significantly stronger than Series 626.



Full width interlocking legs both sides of glazing pocket provides added strength and support for heavy double glazing up to 30mm.



We recommend all commercial framing systems are installed with sub-sill. The sill is fixed to sub-sill for improved performance under ultimate negative wind loads.



Will accept double glazed awning window sashes.

GENERAL

Max Panel Height
Various

Max Panel Width
Various

Max Glass Thickness
30mm

Frame Depth
225mm

ENERGY

UW Range
3.2 - 6.8

SHGC Range
0.22 - 0.64

WEATHER

Maximum Water
1200Pa.

ACOUSTICS

This product has not been acoustics tested.