



KEY FEATURES

- A clean compact lever handle with up to three point locking. Turning the key activates locking rods at top and bottom of the door. Available in 316-grade stainless steel and painted finish.
- Single or multi-point locking options.
- Stainless steel furniture option.
- Available in a range of standard and special powdercoat finishes to match your door.




FINISHING

ANDO™ pulls are fitted both sides of the stile. Designed to suit our architectural and commercial sliding doors.




SNIB KEYS

ANDO™ pulls available in 316 grade stainless steel or powder coat over stainless steel. Designed for use with commercial sliding door locks.



DUMMY LOCK

We have designed custom injection moulded nylon spacers to position the spring loaded lock keeper in the right location.



MULTI-POINT LOCK

The image above shows the shoot bolts on non-thermal commercial doors fitted with multi-point locks.

DIMENSIONS

Height	215mm
Width	125mm
Depth	55mm

SUITABLE FOR USE WITH

-  Series 549 Residential Entry Door
-  Series 548 Designer Bi-fold Door
-  Series 548 Designer Hinged Door
-  Series 729 ThermalHEART® Hinged Door
-  Series 730 ThermalHEART® Bi-fold Door
-  Series 410 FoldMASTER™ Bi-fold Door
-  Series 411 ViewMASTER™ Bi-fold Door
-  Series 412 ViewMASTER™ Bi-fold Door
-  Series 650 Architectural Hinged Door

