



KEY FEATURES

- This swivel bi-fold operator throws locking bolts into the frame at top and bottom of the panel. Optional key-locking (separately installed) is available.
- Having an operator handle located centrally on say a bi-fold door removes the need to bend down or stretch to reach flush bolts that might be located at the ends of the stiles.
- The ICON™ handle is rectangular and crisp with no visible fasteners when handle is in the closed position.
- Furniture only available in 316 grade stainless steel.
- Low line furniture ensures the handle won't strike adjoining panels when doors are in the open position.
- Matching hinged door lever furniture.




NON-KEY LOCKING OPTION

ICON™ bi-fold activator can be supplied non-key locking. The furniture is only available in 316 grade stainless steel.




KEY LOCKING OPTION

ICON™ bi-fold activator can also be supplied in a key locking format.



ADJUSTABLE KEEPERS

On Series 410 Bi-fold doors the keeper in head and sill is adjustable. This allows the panels to be tightened on the frame.



SUPPORT

The bolt tips are supported by extruded aluminium guides. This ensures the bolts fall in the right location and that they can withstand high wind loads

DIMENSIONS

Height	175mm
Width	25mm
Depth	20mm

SUITABLE FOR USE WITH

- Series 546 Designer Bi-fold Window
- Series 548 Designer Bi-fold Door
- Series 730 ThermalHEART® Bi-fold Door
- Series 410 FoldMASTER™ Bi-fold Door
- Series 411 ViewMASTER™ Bi-fold Door
- Series 412 ViewMASTER™ Bi-fold Door
- Series 831 ThermalHEART® Commercial Bi-fold (Top Hung)
- Series 832 ThermalHEART® Commercial Bi-fold (Bottom Rolling)



vantagealuminium.com.au/icon

Subject to individual site conditions and wind loads. Contact AWS Technical Support for more information, e-mail techsupport@awsaustralia.com.au