


KEY FEATURES


- This full vision vertical sliding, sashless double-hung window has been created in 102mm commercial framing.
- 102mm wide perimeter frame designed to make installation into brick veneer and cavity brick easier with built-in nailing fins.
- Sashes can be secured with key locking shoot bolt.
- ClearVENT™ offers clear unobtrusive vision as there are no horizontal central sash rails. As one sash is lifted the other lowers (the sashes are joined via cords and pulleys).
- A fixed sill glass panel can be fitted into the ClearVENT™ window to make it easy to get top ventilation only.
- ClearVENT™ windows can be fitted with external flyscreens within the main frame. No unsightly screws or turn buckles.
- ClearVENT™ vertical sliding sashes can also be installed into Series 50 or 51 hinged and Bi-fold door panels.



We offer standard double-hung sashes as shown above right and sashes with fixed lower panel to shield the lower opening when sashes are opened.



Press button key lock is standard on Series 464 ClearVENT™ sashes.



Alternative bold 44mm wide jamb with built-in nailing fin/weather bar. Both 30mm standard and 44mm wide nailing fin frames will accept height adjustable galvanised building-in lugs.



Integrated screening option available. Standard 30mm jamb with built-in nailing fin/weather bar into brick veneer wall illustrated above.

GENERAL

Max Panel Height*
1526mm

Max Panel Width*
1210mm

Max Glass Thickness
6.38mm

Frame Depth
102mm

ENERGY

UW Range
N/A

SHGC Range
N/A

WEATHER

Maximum Water
300 Pa.

ACOUSTICS

6mm Float
RW26(0:0)

Based on test carried out on similar Series 614 double-hung.



*Dimensions subject to individual site conditions.
elevatealuminium.com.au/464