

KEY FEATURES


- Series 105 Partition framing system has been designed to be single or double glazed.
- The wide glazing pocket (16.50mm) will accept glass up to 12.50mm thick with 8mm bite.
- The 105mm wide frame will give us about 44mm gap between glass, varies slightly depending on the glass thickness.
- Three glazing bead options: 90 degree square bead, 45 degree splayed bead, 25 degree splayed bead.
- The splayed beads shed dust – ideal for projects where dust collection platforms are a problem.
- The silica gel crystals are fitted under the snap-on cover: This cover is designed to be removed in the future when crystals need to be replaced.
- Slim, wide or shadow line perimeter frame options.
- Hinge doors can be swung off mullions.
- Not designed for external weather resisting applications.




Double glazed mullion will accept two monolithic sheets of glass up to 12.50mm thick. This creates approximately 44mm gap between for improved acoustic performance.



Single glazed mullion option for traditional partitioning applications.



Double glazed sill shown above.



Single glazed sill shown above.

GENERAL

Max Panel Height
Various

Max Panel Width
Various

Max Glass Thickness
12.50mm

Frame Depth
105mm

ENERGY

UW Range
N/A

SHGC Range
N/A

WEATHER

Not designed for external weather resisting applications.

ACOUSTICS

6.38mm/40Air/6.38mm
40 (-3,-8)

10.38mm/40Air/6.38mm
44 (-1,-6)

10.38mm/40Air/10.38mm
45 (-1,-5)

10.38mm
35 (-1,-2)